

**PATENT****PENDING CLAIMS AS AMENDED**

Please amend the claims as follows:

1. (Previously Presented) A method of framing a payload, comprising:  
delimiting frame boundaries of a payload;  
calculating an initial checksum as a function of a first subset of the payload and a length field of the payload;  
calculating a final checksum as a function of a second subset of the payload and the length field of the payload; and  
appending the initial checksum and the final checksum to the payload within the frame boundaries.
2. (Previously Presented) The method of claim 1 wherein the frame delimitation comprises appending a preamble to the beginning of the payload, the preamble having the initial checksum.
3. (Previously Presented) The method of claim 2 wherein the payload comprises a plurality of bytes, and the first subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble.
4. (Previously Presented) The method of claim 3 further comprising disposing in the preamble the length field which indicates the number of bytes in the payload.
5. (Previously Presented) The method of claim 4 wherein the calculation of the initial checksum comprises exclusive OR-ing the first subset of the payload and the length field.
6. (canceled)

**PATENT**

7. (Previously Presented) The method of claim 5 wherein the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the last byte of the payload, and wherein the calculation of the final checksum comprises exclusive OR-ing the second subset of the payload and the length field.

8. (Previously Presented) The method of claim 1 wherein the frame delimitation comprises appending final checksum to the end of the payload.

9. (Previously Presented) The method of claim 8 wherein the payload comprises a plurality of bytes, and the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the last byte of the payload.

10. (Previously Presented) The method of claim 9 wherein the frame delimitation comprises appending a preamble having the length field to the beginning of the payload

11. (Previously Presented) The method of claim 10 wherein the calculation of the initial checksum comprises exclusive OR-ing the first subset of the payload and the length field.

12. (Previously Presented) A method of framing a payload, comprising:  
delimiting frame boundaries of a payload;  
calculating a value as a function of a subset of the payload; and  
appending the value to the payload within the frame boundaries, wherein the payload comprises a maximum number of bytes, and wherein the frame delimitation comprises appending a preamble to the beginning of the payload, the preamble comprising a start flag having a first byte, the value following the start flag, and a length field following the value, the length field indicating the number of bytes in the payload, and wherein the value and a portion of the length field comprises a second byte, the second byte being limited to a subset of byte values due to the maximum number of bytes in the payload, the method further

**PATENT**

comprising selecting a start flag having a byte value different from the subset of byte values available for the second byte.

13. (original) The method of claim 12 wherein the value comprises 5-bits and the length field comprises at least 3-bits, the second byte comprising the 5-bit value followed by the three most significant bits of the length field.

14-17 (canceled)

18. (Previously Presented) A method of determining a valid payload in a frame, comprising:

- identifying a frame having a payload with a first value appended thereto;
- calculating a second value as a function of a subset of the payload;
- comparing the second value to the first value;
- detecting a valid payload as a function of the comparison wherein the payload comprises a plurality of bytes; and
- identifying a length field in the frame indicating the number of bytes in the payload, wherein the calculation of the second value is further a function of the length field, wherein the subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the calculation of the second value comprises exclusive OR-ing the subset of the payload and the length field.

19. (canceled)

20-22 (canceled)

23. (Previously Presented) A method of determining a valid payload in a frame, comprising:

- identifying a frame having a payload with a first value appended thereto;
- calculating a second value as a function of a subset of the payload;

## PATENT

comparing the second value to the first value;  
detecting a valid payload as a function of the comparison, wherein the frame including the payload comprises a plurality of bytes;  
receiving the frame in a serial byte stream;  
counting the number of payload bytes received within a predetermined time;  
declaring an invalid frame if the payload byte count within the predetermined time is below a threshold;  
recounting the number of payload bytes received within a second predetermined time if the payload byte within the predetermined time exceeds the threshold.

24 – 27 (canceled)

28. (Currently Amended) A method of determining a valid payload in a frame, comprising:

identifying a frame having a payload with a first value appended thereto;  
calculating a second value as a function of a subset of the payload;  
comparing the second value to the first value; and  
detecting a valid payload as a function of the comparison, wherein the first value is appended to the beginning of the payload, the frame further comprising a third value appended to the end of the payload, the method further comprising calculating a fourth value as a function of a second subset of the payload, and comparing the fourth value to the third value, the valid payload detection being a function of both the comparison of the first value to the second value and the comparison of the third value to the fourth value, wherein valid payload detection further comprises confirming a stop flag within the frame immediately following the third value, wherein the payload comprises a plurality of bytes, the method further comprising identifying a length field in the frame indicating the number of bytes in the payload, the calculation of the second value and the calculation of the fourth value are both further a function of the length field ~~The method of claim 27~~  
wherein the subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the second subset of the payload comprises the third,

## PATENT

fourth and fifth bytes of the payload following the preamble and the last byte of the payload.

29. (Previously presented) The method of claim 28 wherein calculation of the second value comprises exclusive OR-ing the subset of the payload and the length field, and the calculation of the fourth value comprises exclusive OR-ing the second subset of the payload and the length field.

30. (Previously presented) Computer-readable media embodying a program of instructions executable by a computer to perform a method of framing a payload, the method comprising:

- delimiting frame boundaries of a payload;
- calculating an initial checksum as a function of a first subset of the payload and a length field of the payload;
- calculating a final checksum as a function of a second subset of the payload and the length field of the payload; and
- appending the initial checksum and the final checksum to the payload within the frame boundaries.

31. (Previously presented) The computer-readable media of claim 30 wherein the frame delimitation comprises appending a preamble to the beginning of the payload, the preamble having the initial checksum.

32. (Previously presented) The computer-readable media of claim 31 wherein the payload comprises a plurality of bytes, and the first subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble.

33. (Previously presented) The computer-readable media of claim 32 wherein the method further comprises disposing in the preamble the length field which indicates the number of bytes in the payload.

**PATENT**

34. (Previously presented) The computer-readable media of claim 33 wherein the calculation of the initial checksum comprises exclusive OR-ing the first subset of the payload and the length field.

35. (canceled)

36. (Previously presented) The computer-readable media of claim 34 wherein the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the last byte of the payload, and wherein the calculation of the final checksum comprises exclusive OR-ing the second subset of the payload and the length field.

37. (Previously presented) The computer-readable media of claim 30 wherein the frame delimitation comprises appending the final checksum to the end of the payload.

38. (Previously presented) The computer-readable media of claim 37 wherein the payload comprises a plurality of bytes, and the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the last byte of the payload.

39. (Previously presented) The computer-readable media of claim 38 wherein the frame delimitation comprises appending a preamble having the length field to the beginning of the payload.

40. (Previously presented) The computer-readable media of claim 39 wherein the calculation of the initial checksum comprises exclusive OR-ing the first subset of the payload and the length field.

41. (Previously presented) Computer-readable media embodying a program of instructions executable by a computer to perform a method of framing a payload, the method comprising:

## PATENT

delimiting frame boundaries of a payload;

calculating a value as a function of a subset of the payload; and

appending the value to the payload within the frame boundaries, wherein the payload comprises a maximum number of bytes, and wherein the frame delimitation comprises appending a preamble to the beginning of the payload, the preamble comprising a start flag having a first byte, the value following the start flag, and a length field following the value, the length field indicating the number of bytes in the payload, and wherein the value and a portion of the length field comprises a second byte, the second byte being limited to a subset of byte values due to the maximum number of bytes in the payload, the method further comprising selecting a start flag having a byte value different from the subset of byte values available for the second byte.

42. (original) The computer-readable media of claim 41 wherein the value comprises 5-bits and the length field comprises at least 3-bits, the second byte comprising the 5-bit value followed by the three most significant bits of the length field.

43-46 (canceled)

47. (Previously presented) Computer-readable media embodying a program of instructions executable by a computer to perform a method of determining a valid payload in a frame, the method comprising:

identifying a frame having a payload with a first value appended thereto;

calculating a second value as a function of a subset of the payload;

comparing the second value to the first value; and

detecting a valid payload as a function of the comparison wherein the payload comprises a plurality of bytes, the method further comprising identifying a length field in the frame indicating the number of bytes in the payload wherein the calculation of the second value is further a function of the length field, wherein the subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the

## PATENT

calculation of the second value comprises exclusive OR-ing the subset of the payload and the length field.

48-51 (canceled)

52. (Previously presented) Computer-readable media embodying a program of instructions executable by a computer to perform a method of determining a valid payload in a frame, the method comprising:

identifying a frame having a payload with a first value appended thereto;

calculating a second value as a function of a subset of the payload;

comparing the second value to the first value; and

detecting a valid payload as a function of the comparison wherein the frame including the payload comprises a plurality of bytes, the method further comprising receiving the frame in a serial byte stream, counting the number of payload bytes received within a predetermined time, and declaring an invalid frame if the payload byte count within the predetermined time is below a threshold, wherein the method further comprises recounting the number of payload bytes received within a second predetermined time if the payload byte within the predetermined time exceeds the threshold.

53 – 56 (Canceled)

57. (Currently amended) Computer-readable media embodying a program of instructions executable by a computer to perform a method of determining a valid payload in a frame, the method comprising:

identifying a frame having a payload with a first value appended thereto;

calculating a second value as a function of a subset of the payload;

comparing the second value to the first value; and

detecting a valid payload as a function of the comparison.



## PATENT

wherein the first value is appended to the beginning of the payload, the frame further comprising a third value appended to the end of the payload, the method further comprising calculating a fourth value as a function of a second subset of the payload, and comparing the fourth value to the third value, the valid payload detection being a function of both the comparison of the first value to the second value and the comparison of the third value to the fourth value wherein valid payload detection further comprises confirming a stop flag within the frame immediately following the third value wherein the payload comprises a plurality of bytes, the method further comprising identifying a length field in the frame indicating the number of bytes in the payload wherein the calculation of the second value and the calculation of the fourth value are both further a function of the length field ~~The computer-readable media of claim 56~~ wherein the subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble and the last byte of the payload.

58. (Previously Presented) The computer-readable media of claim 57 wherein calculation of the second value comprises exclusive OR-ing the subset of the payload and the length field, and the calculation of the fourth value comprises exclusive OR-ing the second subset of the payload and the length field.

59. (Previously presented) A communications device, comprising:

a processor configured to delimit frame boundaries of a payload, calculate an initial checksum as a function of a first subset of the payload and a length field of the payload, calculate a final checksum as a function of a second subset of the payload and the length field of the payload, and append the initial checksum and the final checksum to the payload within the frame boundaries; and

a transmitter configured to transmit the processed frame.

60. (Previously presented) The communications device of claim 59 wherein the processor is further configured to append a preamble to the beginning of the payload, the preamble having the initial checksum.

## PATENT

61. (Previously presented) The communications device of claim 60 wherein the processor is further configured append the final checksum to the end of the payload within the frame boundaries.

62. (Previously presented) The communications device of claim 61 wherein the payload comprises a plurality of bytes, the processor further configured to dispose in the preamble the length field which indicates the number of bytes in the payload.

63. (Previously presented) The communications device of claim 62 wherein the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the last byte of the payload, the processor further being configured to calculate the final checksum by exclusive or-ing the second subset of the payload and the length field.

64. (Previously presented) The communications device of claim 59 wherein the payload comprises a plurality of bytes, the processor further being configured to dispose in the preamble the length field which indicates the number of bytes in the payload.

65. (Previously presented) The communications device of claim 64 wherein the first subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, the processor further being configured to calculate the initial checksum by exclusive OR-ing the first subset of the payload and the length field.

66. (original) The communications device of claim 59 wherein the transmitter comprises a wireless transmitter.

## PATENT

67. (original) The communications device of claim 66 wherein the transmitter comprises a code division multiple access transmitter.

68 -72 (canceled)

73. (Previously presented) A communications device, comprising:  
a receiver configured to receive a frame having a payload with a first value appended thereto; and  
a processor configured to calculate a second value as a function of a subset of the payload, compare the second value to the first value, and detect a valid payload as a function of the comparison wherein the payload comprises a plurality of bytes, the processor further being configured to identify a length field in the frame indicating the number of bytes in the payload, and to calculate the second value as a function of the subset of the payload and the length field, wherein the frame further comprises a preamble having the first value appended to the beginning of the payload, and wherein the subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, the processor further being configured to calculate the second value by exclusive OR-ing the subset of the payload and the length field.

74. (Previously Presented) The communications device of claim 73 wherein the processor is further configured to determine whether the number of payload bytes indicated by the length field exceeds a threshold, the valid payload detection by the processor further being a function of the length field determination.

75. (Previously presented) The communications device of claim 73 wherein the receiver is further configured to receive the frame in a serial byte stream, and wherein the processor is further configured to determine whether all the payload bytes are received within a predetermined time from receipt of the first payload byte, the valid frame detection by the processor further being a function of the payload byte determination.

## PATENT

76. (original) The communications device of claim 75 wherein the processor is further configured to identify a length field in the frame indicating the number of bytes in the payload, the payload byte determination being a function of the length field indication.

77. (Previously presented) The communications device of claim 74 wherein the receiver is further configured to receive the frame in a serial byte stream, and wherein the processor is further configured to count the number of payload bytes received within a predetermined time, and declare an invalid frame if the payload byte count within the predetermined time is below a threshold.

78. (original) The communications device of claim 77 wherein the processor is further configured to recount the number of payload bytes received within a second predetermined time if the payload byte within the predetermined time exceeds the threshold.

79 – 80 (canceled)

81. (currently amended) A communications device, comprising:  
a receiver configured to receive frame having a payload with a first value  
appended thereto; and  
a processor configured to calculate a second value as a function of a subset of the  
payload, compare the second value to the first value, and detect a valid payload as a function of  
the comparison, wherein the payload comprises a plurality of bytes, the processor further being  
configured to identify a length field in the frame indicating the number of bytes in the payload,  
the calculation of both the second and fourth value by the processor being further a function of  
the length field wherein the first value is appended to the beginning of the payload, the frame  
further comprising a third value appended to the end of the payload, the processor further being  
configured to calculate a fourth value as a function of a second subset of the payload, and  
compare the fourth value to the third value, the valid payload detection by the processor being a  
function of both the comparison of the first value to the second value and the comparison of the  
third value to the fourth value ~~The communications device of claim 80 wherein the subset of the~~

**PATENT**

payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble and the last byte of the payload.

82. (Previously presented) The communications device of claim 81 wherein the processor is further configured to calculate the second value by exclusive OR-ing the subset of the payload and the length field, and calculate the fourth value by exclusive OR-ing the second subset of the payload and the length field.

83 – 87 (Canceled)

88. (Previously presented) A communications device, comprising:

means for delimiting frame boundaries of a payload;

calculation means for:

calculating an initial checksum as a function of a first subset of the payload and a length of the payload,

calculating a final checksum as a function of a second subset of the payload and the length of the payload; and

appending means for appending the initial checksum and the final checksum to the payload within the frame boundaries.

89. (Previously presented) The communications device of claim 88 wherein the appending means appends a preamble to the beginning of the payload, the preamble having the initial checksum .

90. (canceled)

91. (Previously presented) The communications device of claim 89 wherein the payload comprises a plurality of bytes, and wherein the appending means disposes in the preamble the length field which indicates the number of bytes in the payload.

## PATENT

92. (Previously presented) The communications device of claim 91 wherein the second subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and the last byte of the payload, and wherein the calculation means calculates the final checksum by exclusive OR-ing the second subset of the payload and the length field.

93. (Previously presented) The communications device of claim 89 wherein the payload comprises a plurality of bytes, and wherein the appending means disposes in the preamble the length field which indicates the number of bytes in the payload, and the calculating means calculates the initial checksum as a function of the first subset of the payload and the length field.

94. (Previously presented) The communications device of claim 93 wherein the first subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and wherein the calculation means calculates the initial checksum by exclusive OR-ing the first subset of the payload and the length field.

95-96 (canceled)

97. (Previously presented) A communications device, comprising:  
means for identifying a frame having a payload with a first value appended thereto;

calculation means for calculating a second value as a function of a subset of the payload;

comparison means for comparing the second value to the first value; and

detection means for detecting a valid payload as a function of the comparison,

wherein the payload comprises a plurality of bytes, the communications device further comprising means for identifying a length field in the frame indicating the number of bytes in the payload; wherein the calculation means calculates the second value as a function of the subset of the payload and the length field, wherein the frame further comprises a preamble having the first

**PATENT**

value appended to the beginning of the payload, and the subset of the payload comprises the third, fourth and fifth bytes of the payload following the preamble, and wherein the calculation means calculates the second value by exclusive OR-ing the subset of the payload and the length field.

98. (Previously presented) The communications device of claim 97 further comprising means for determining whether the number of payload bytes indicated by the length field exceeds a threshold, and wherein the detection means detects a valid payload further as a function of the length field determination.

99. (Previously presented) The communications device of claim 97, further comprising means for receiving the frame in a serial byte stream, and means for determining whether all the payload bytes are received within a predetermined time from receipt of the first payload byte, wherein the detection means detects a valid payload further as a function of the payload byte determination.

100. (Previously presented) The communications device of claim 97, further comprising means for receiving the frame in a serial byte stream, means for counting the number of payload bytes received within a predetermined time, and means for declaring an invalid frame if the payload byte count within the predetermined time is below a threshold.

101. (original) The communications device of claim 100 further comprising means for recounting the number of payload bytes received within a second predetermined time if the payload byte within the predetermined time exceeds the threshold.

## PATENT

102 - 103 (canceled)

104. (Currently Amended) A communications device, comprising:  
means for identifying a frame having a payload with a first value appended  
thereto;  
calculation means for calculating a second value as a function of a subset of the  
payload;  
comparison means for comparing the second value to the first value; and  
detection means for detecting a valid payload as a function of the comparison. ~~The~~  
~~communications device of claim 103~~ wherein the subset of the payload comprises the third,  
fourth and fifth bytes of the payload following the preamble, and the second subset of the  
payload comprises the third, fourth and fifth bytes of the payload following the preamble and the  
last byte of the payload, wherein the first value is appended to the beginning of the payload, the  
frame further comprising a third value appended to the end of the payload, the communications  
device further comprising second calculation means for calculating a fourth value as a function of  
a second subset of the payload, and second comparison means for comparing the fourth value to  
the third value, wherein the detection means detects a valid payload as a function of both the  
comparison of the first value to the second value and the comparison of the third value to the  
fourth value, wherein the payload comprises a plurality of bytes, the communications device  
further comprising means for identifying a length field in the frame indicating the number of  
bytes in the payload, the calculation means and the second calculation means each calculating its  
respective second and fourth further as a function of the length field.



## PATENT

105. (Previously Presented) The communications device of claim 104 wherein the calculation means calculates the second value by exclusive OR-ing the subset of the payload and the length field, and the second calculation means calculates the fourth value by exclusive OR-ing the second subset of the payload and the length field.